

PRODUCT DATA SHEET

Product name

Cleft palings

Species

Robinia — *Robinia pseudoacacia* L.

Other names: black locust, false acacia, acacia. Known as robinia in the timber trade.

Origin

Romania – Full traceability in compliance with the EUDR regulation

Product description


Roll fencing made from robinia paling slats joined by galvanised double-twisted wire. Used for demarcation, protection and landscaping.

Paling slat characteristics

- Sawn triangular section
- Circ.: 9 to 12 cm (± 1 cm)
- Width: 3 to 4 cm
- Pointed slats
- Density: 780–820 kg/m³
- Yellow-brown hue
- High-strength hardwood
- Fresh (green) or slightly dried timber

Wire characteristics

- Galvanised wire $\varnothing$ 1,8 mm – strength 550 N/mm²
- Hot-dip galvanising (min. 50 g/m² zinc)
- Double-twist assembly – 2 to 5 rows
- 4 wires per row



Available dimensions

- Heights: 0,50 / 0,80 / 1,00 / 1,20 / 1,50 / 1,80 / 2,00 m
- Roll lengths: 5 m or 10 m
- Slat spacing: 1 to 10 cm

Durability

- Class 4 (standard EN 335)
- Non-impregnable wood, untreated
- Service life up to 30 years depending on exposure

Applications

Dune and coastal protection – rustic fencing – landscaping – wildlife protection – path demarcation.

Weathering

Natural greying – colour variation – possible surface cracking – slight bowing of the slats.

Maintenance

No maintenance required – no treatment needed.

Options

- Unpointed slats
- Sanded slats
- Alternating heights
- FSC® 100 % certification on request



Cleft paling H 1,5 m
Spacing 3–4 cm



Cleft paling H 1,5 m
Square stake 7 × 7 cm



Cleft paling
Slats of different heights



Cleft paling
Sanded slats



Cleft paling
Galvanised wires $\varnothing$ 1,8 mm



Cleft paling – H 1,2 m
Spacing 3–4 cm



Packaging: Number of <u>rolls of 5 m</u> per pallet		Spacing between slats (cm)								
		1-2	2-3	3-4	4-5	5-6	6-7	7-8	8-9	9-10
Height (m)	0,5	30	30	30	30	30	30	30	30	30
	0,8	12	12	12	15	15	15	15	15	15
	1,0	12	12	12	15	15	15	15	15	15
	1,2	12	12	12	15	15	15	15	15	15
	1,5	12	12	12	15	15	15	15	15	15
	1,8	12	12	12	15	15	15	15	15	15
	2,0	12	12	12	15	15	15	15	15	15
Packaging: Number of <u>rolls of 10 m</u> per pallet		Spacing between slats (cm)								
		1-2	2-3	3-4	4-5	5-6	6-7	7-8	8-9	9-10
Height (m)	0,5	14	14	14	14	14	14	14	14	14
	0,8	8	8	8	8	8	10	10	10	10
	1,0	8	8	8	8	8	10	10	10	10
	1,2	8	8	8	8	8	10	10	10	10
	1,5	-	-	-	-	-	-	10	10	-
	1,8	-	-	-	-	-	-	-	-	-
	2,0	-	-	-	-	-	-	-	-	-

(-) not available

Unit weight of a 5 m roll (kg)		Spacing between slats (cm)								
		1-2	2-3	3-4	4-5	5-6	6-7	7-8	8-9	9-10
Height (m)	0,5	27	22	16	15	14	12	11	10	9
	0,8	43	35	26	23	22	20	18	16	15
	1,0	54	44	32	29	28	25	22	20	19
	1,2	64	52	39	35	33	30	26	24	23
	1,5	81	65	48	44	42	37	33	29	28
	1,8	97	78	58	52	50	45	39	35	34
	2,0	107	87	65	58	56	50	44	39	38

Palletisation - pallet dimensions (based on cleft paling height)			
Cleft paling height (m)	Pallet width (m)	Pallet height (m)	Pallet depth (m)
0,5	1	1,2	1,2
0,8	1	1,2	1,2
1	1	1,2	1,2
1,2	1,2	1,2	1,2
1,5	1,5	1,2	1,2
1,8	1,8	1,2	1,2
2	2	1,2	1,2



Stackable cleft paling pallets

Number of slats per linear metre of paling		Spacing between slats (cm)								
		1-2	2-3	3-4	4-5	5-6	6-7	7-8	8-9	9-10
Height (m)	0,5	18	16	15	13	12	11	10	9	8
	0,8	18	16	15	13	12	11	10	9	8
	1,0	18	16	15	13	12	11	10	9	8
	1,2	18	16	15	13	12	11	10	9	8
	1,5	18	16	15	13	12	11	10	9	8
	1,8	18	16	15	13	12	11	10	9	8
	2,0	18	16	15	13	12	11	10	9	8



Producer contact details

Srl. Xylo Impact – Strada Principala 115A – 337291 Teiu – Romania

VAT number: RO33531190

IBAN: BE38 9140 1467 2472

BIC: FXBBBEBBXXX

Acacia Poles, a trade name of Xylo Impact

FSC® certification: SGSCH-COC-011793 – FSC® licence C153588

Contact us: info@acaciapoles.com

More info: www.acaciapoles.com

Non-contractual document, provided for information only (photos included). Specifications may change without notice; in case of discrepancy, only the general terms of sale apply.

© Xylo Impact SRL — all rights reserved, products marketed under the Acacia Poles brand. Any reproduction, even partial, is prohibited without prior authorisation.

Document issued on 25/02/2026.