

PRODUCT DATA SHEET



Product name

Eucalyptus poles

Species

Eucalyptus grandis

Origin

South Africa, full traceability in compliance with EUDR.

Product description

Thin round eucalyptus stems, debarked and sanded

Pole characteristics

- Eucalyptus poles impregnated with copper azole, resistant to weather, insects and fungi.
- Several diameter classes available
- Diameter: 1,5–3,5 cm / 3–5 cm (± 1 cm)
 - Density: 400–500 kg/m³
 - White and light brown hue
 - Light, easy-to-work timber
- Fresh (green) or slightly dried timber

Available dimensions

- Lengths: 1 / 1,2 / 1,5 / 1,8 / 2,25 / 3 / 3,6 / 4,5 m
- Diameters: 1,5–3,5 / 3–5 cm

Durability

- Class 3 (standard EN 335)
- Impregnable wood, treated
- Service life up to 20 years depending on exposure

Applications

Pergola roofing and other outdoor structures

Weathering

Natural greying – colour variation – possible surface cracking.

Maintenance

No maintenance required – no treatment needed.

Options

Storage of poles for drying



Loading eucalyptus poles



Pergola roof, eucalyptus poles



Packaging – poles per pallet	
Diameter (cm)	Quantity
1,5 – 2,5	700
3 – 5	500

Pole weight (kg)								
Diameter (cm)	Length (m)							
	1	1,2	1,5	1,8	2,25	3	3,6	4,5
1,5 – 2,5	0,2	0,3	0,3	0,4	0,5	0,7	0,8	1
3 – 5	0,6	0,7	0,8	1	1,3	1,7	2	2,5



Producer contact details

Srl. Xylo Impact – Strada Principala 115A – 337291 Teiu – Romania

VAT number: RO33531190

IBAN: BE38 9140 1467 2472

BIC: FXBBBEBBXXX

Acacia Poles, a trade name of Xylo Impact

Contact us: info@acaciapoles.com

More info: www.acaciapoles.com

Non-contractual document, provided for information only (photos included). Specifications may change without notice; in case of discrepancy, only the general terms of sale apply.

© Xylo Impact SRL — all rights reserved, products marketed under the Acacia Poles brand. Any reproduction, even partial, is prohibited without prior authorisation.

Document issued on 25/02/2026.